



# NTN BEARING USA CORP.

1.772 Inch | 45 Millimeter x 3.125 Inch | 79.38  
 Millimeter x 2.252 Inch | 57.2 Millimeter  
 REXNORD ZEP2045MM Pillow Block Bearings



Bearing No. ZEP2045MM

ZEP2045MM Bearing 2D drawings and 3D CAD models

|                           |  |
|---------------------------|--|
| Category                  | Pillow Block Bearings  |
| Inventory                 | 0.0  |
| Manufacturer Name         | REXNORD  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 5.357  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Concentric Collar  |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 16 Millimeter  |
| Relubricatable            | Yes  |
| Insert Part Number        | 2045MMU  |
| Seals                     | Clearance Seal   |
| Housing Configuration     | 1 Piece Solid  |
| Inch - Metric             | Metric   |
| Other Features            | Double Row   Single Collar  <br>With Set Screw   |
| Long Description          | 2 Bolt Pillow Block; 45MM<br>Bore; 57.2MM Base to<br>Center Height; Concentric<br>Collar Mount; Spherical<br>Roller Bearing; 154MM<br>Minimum Bolt Spacing;<br>184.15MM Bolt Spacing |



## NTN BEARING USA CORP.

|                               |   |
|-------------------------------|---|
|                               | Maximum; Relubricatable;<br>Cast Iron; C                    |
| Category                      | Pillow Block  |
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.80   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer URL              | <a href="http://www.rexnord.com">http://www.rexnord.com</a> |
| Manufacturer Item Number      | ZEP2045MM   |
| Manufacturer Internal Number  | 6801996   |
| Weight / LBS                  | 11.8  |
| d                             | 1.772 Inch   45 Millimeter                                  |
| B                             | 2.252 Inch   57.2 Millimeter                                |
| D                             | 3.125 Inch   79.38<br>Millimeter                            |
| Bolt Spacing Maximum          | 7.25 Inch   184.15Millimeter                                |
| Bolt Spacing Minimum          | 6.063 Inch   154Millimeter                                  |
| Nominal Bolt Center to Center | 6.7 Inch   170 Millimeter                                   |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter  |